Application No.: 09/965417

Case No.: 56233US002

## Amendments to the Claims:

The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method of making a film, comprising: forming a first alignment layer on a surface of a polarizing element; disposing a liquid crystal material on the first alignment layer; and

forming an aligned liquid crystal layer from the liquid crystal material to produce a polarization rotator element configured and arranged to rotate the polarization of at least a portion of the light that is transmitted by the polarizing element by a fixed angle of at least 5 degrees.

- 2. (original) The method of claim 1, wherein forming a first alignment layer comprises forming a first alignment layer from a portion of the polarizing element.
- 3. (original) The method of claim 2, wherein forming a first alignment layer comprises stretching at least a portion of the polarizing element to form an aligned surface.
- 4. (original) The method of claim 1, wherein forming a first alignment layer comprises forming a first alignment layer on the polarizing element.
- 5. (original) The method of claim 1, further comprising disposing a second alignment layer on the liquid crystal material.
- 6. (original) The method of claim 5, wherein disposing a second alignment layer comprises forming a second alignment layer on the liquid crystal material.

Application No.: 09/965417

Case No.: 56233US002

- 7. (original) The method of claim 5, wherein disposing a second alignment layer comprises forming the second alignment layer on a substrate and disposing the second alignment layer and substrate on the liquid crystal material.
- 8. (original) The method of claim 7, further comprising disposing liquid crystal material on the second alignment layer and contacting the liquid crystal material on the second alignment layer with the liquid crystal material on the first alignment layer.
- 9. (original) The method of claim 7, wherein forming the second alignment layer on a substrate comprises forming the second alignment layer on a substrate comprising a second polarizing element.
- 10. (original) The method of claim 9, wherein forming an aligned liquid crystal layer comprises forming an aligned liquid crystal layer from the liquid crystal material, wherein the aligned liquid crystal layer is configured and arranged to rotate a polarization of light normally incident on the aligned liquid crystal layer from a polarization axis of the polarizing element to the polarization axis of the second polarizing element which differs by at least 5 degrees.
- 11. (currently amended) The method of claim 10, wherein forming an aligned liquid crystal layer comprises forming the aligned liquid crystal layer with a twist angle that is substantially smaller than a phase retardation of the polarization rotator element.
- 12. (original) The method of claim 1, wherein forming an aligned liquid crystal layer comprises forming an aligned liquid crystal layer from the liquid crystal material, wherein the aligned liquid crystal layer is configured and arranged to rotate a polarization of light normally incident on the aligned liquid crystal layer by at least 5 degrees.
- 13. (currently amended) The method of claim 12, wherein forming an aligned liquid crystal layer comprises forming the aligned liquid crystal layer with a twist angle that is substantially smaller than a phase retardation of the polarization rotator element.

Application No.: 09/965417

Case No.: 56233US002

- 14. (original) The method of claim 12, wherein forming an aligned liquid crystal layer comprises forming an aligned liquid crystal layer using only a single alignment layer.
- 15. (currently amended) A method of making a film, comprising:
  forming a first alignment layer on a surface of a polarizing element;
  disposing a liquid crystal material on the first alignment layer;
  disposing at least one additional layer on the liquid crystal material; and
  directing light through the at least one additional layer to the liquid crystal material to
  cure the liquid crystal material and form an aligned liquid crystal layer to produce a polarization
  rotator element configured and arranged to rotate the polarization of at least a portion of the light
  that is transmitted by the polarizing element by a fixed angle of at least 5 degrees.
- 16. (original) The method of claim 15, wherein disposing at least one additional layer comprises disposing a second alignment layer on the liquid crystal material.
- 17. (original) The method of claim 16, wherein disposing a second alignment layer comprises forming the second alignment layer on a substrate and disposing the second alignment layer and substrate on the liquid crystal material.
- 18. (original) The method of claim 16, wherein disposing a second alignment layer and directing light comprise

disposing a photo-orientable material on the liquid crystal material; and directing polarized light at an orientation direction through the photo-orientable material to the liquid crystal material to cure and orient the photo-orientable material at the orientation direction to form the second alignment layer and to cure the liquid crystal material and form an aligned liquid crystal layer to produce a polarization rotator element.

19. (original) The method of claim 16, wherein forming a first alignment layer, disposing a second alignment layer, and directing light comprise

Case No.: 56233US002

disposing a first photo-orientable material on the surface of the polarizing element; disposing a second photo-orientable material on the liquid crystal material; and directing polarized light at an orientation direction through the second photo-orientable material to the liquid crystal material and the first photo-orientable material to a) cure and orient the first photo-orientable material at the orientation direction to form the first alignment layer, b) cure and orient the second photo-orientable material at the orientation direction to form the second alignment layer, and c) cure the liquid crystal material and form an aligned liquid crystal layer to produce a polarization rotator element.

- 20. (original) The method of claim 15, wherein directing light comprises directing ultraviolet light through the at least one additional layer to the liquid crystal material to cure the liquid crystal material and form an aligned liquid crystal layer to produce a polarization rotator element.
  - 21. (currently amended) A method of making a film, comprising: unwinding a first film comprising a polarizing element; forming a first alignment layer on a surface of the polarizing element; disposing a liquid crystal material on the first alignment layer; unwinding a second film;

forming a second alignment layer on a surface of the second film;
contacting the first and second films so that the liquid crystal material is disposed
between the first and second alignment layers; and

forming an aligned liquid crystal layer from the liquid crystal material to produce a polarization rotator element configured and arranged to rotate the polarization of at least a portion of the light that is transmitted by the polarizing element by a fixed angle of at least 5 degrees.

22. (previously presented) The method of claim 21, further comprising forming a liquid crystal material on the second alignment layer prior to contacting the first and second films.

MAY. 24. 2004 3:15PM OIPC 220 12W 01

NO. 4405 P. 8

Application No.: 09/965417

Case No.: 56233US002

23. (previously presented) The method of claim 21, wherein forming an aligned liquid crystal layer comprises directing light through the second film and second alignment layer to the liquid crystal material to cure the liquid crystal material and form an aligned liquid crystal layer to produce a polarization rotator element.